

CT 15

[NEW]

Great Productivity



Scrubs in difficult to reach areas



Solution control (Solenoid valve)



Brush control with soft start



High Performance



CFS (Center Flow System)



High quality and performance vacuum motor



Easy to transport



Extractable recovery tank



Battery level indicator



Ergonomics, User Friendly



Great maneuverability thanks to an optimum weight distribution

Removable recovery tank

The recovery tank can be removed simply without tools to help the operations of dirty water drain and have an easy access to internal compartments.



Technical data		CT15 C	CT15 B
Scrubbing width	mm	350	350
Suction width	mm	450	450
Productivity (max speed)	m ² /h	1300	1300
Number of brushes		1 (disc)	1 (disc)
Solution tank capacity	l	16	16
Recovery tank capacity	l	19	19
Power supply		220 - 240V 50 Hz	24V (2x12V)
Max speed	Km/h	3,5	3,5
Weight	Kg	37,5	59 (batteries included)
Dimensions (LxWxH)	mm	395x740x535	395x740x535

CT 15



Low Maintenance Cost



Brush replacement without tools



Squeegee blades can be used on 4 sides before replacement



Easy access to internal compartments



Easy to use control panel

The control panel, easy to use and intuitive, allows to activate the brush, the vacuum motor and water supply.

Robust Construction



Tanks and surrounding body in high density polyethylene



Oil bath reduction gear box



Brush head designed to absorb harsh impact (optional)



Squeegee system designed to absorb harsh impact



Panel control switches protected against water and humidity



Height-adjustable handlebar

It is possible to adjust the handlebar height during work to ease the cleaning operations in difficult to reach areas.

