

CT 90

Great Productivity



Huge solution tank capacity in minimum external space



Extensive running time (Large battery compartment)



Solution control with automatic stop (Solenoid valve)



Brush control with automatic "delayed" stop



CT 90



High Performance



Solution distribution from brush center



CWS (Constant Weight System)



Exclusive squeegee system assures high performance at low cost



High quality and performance vacuum motor

Ergonomics, User Friendly



Great manoeuvrability thanks to an optimum weight distribution



Great visibility whilst working



Designed to assure minimum noise levels



Easy to use control panel



Battery level indicator



Recovery tank discharge point and hose at maximum height



Solution tank can be tilted



External battery charger plug



On board charger can be fitted also at a later stage

Low Maintenance Costs



Inlet and outlet filters for maximum solution tank protection



AFS (Anti Foam System)



Brush replacement without tools



Squeegee blade can be used on 4 sides before replacement



Squeegee assembly and blades replacement without tools



Easy access to internal compartments



CT 90



BT60 version

Robust Construction



Tanks and surrounding body in high density polyethylene



Oil bath reduction gear box



Brush head designed to absorb harsh impact



Squeegee system designed to absorb harsh impact



Panel control switches protected against water and humidity



Technical data		CT90 BT60	CT90 BT70	CT90 BT85
Scrubbing width	mm	600	700	850
Suction width	mm	816	942	942
Productivity (at max speed)	m ² /h	2700	3150	3825
Number of brushes		2 (disc)	2 (disc)	2 (disc)
Solution tank capacity	l	85	85	85
Recovery tank capacity	l	90	90	90
Power supply		24V (4x6V)	24V (4x6V)	24V (4x6V)
Max speed	Km/h	4,5 (electric)	4,5 (electric)	4,5 (electric)
Weight (net)	Kg	97,6	98,4	104
Dimensions (LxWxH)	mm	1328x680x1025	1358x748x1025	1446x893x1025

CT 90



Exclusive squeegee system assures high performance at low cost

Incomparable drying results even on the most difficult surfaces thanks to a very unique design.



Huge tank capacity in minimum external space

90-95 litre capacity tanks make this model very unique in its category.



Solution control with automatic stop

Saves water and save chemicals. Solution flow stops and starts upon brush command.



Water level control on both tanks. Maximum protection for the vacuum motor (Water Level Sensor)

1. The vacuum motor is mounted in the highest part of the machine. A sensor shuts off the vacuum motor when the dirty water tank is full.

2. When the dirty water tank is full, the left LED comes on and the vacuum motor shuts down. The right LED indicates when the detergent solution has reached the reserve and there is enough detergent left for about two minutes.



Brush control with automatic delayed stop

Saves brush wear and protects delicate surfaces. Brush rotation stops (3 sec. delay) and starts upon brush command.



Recovery tank can be tilted

Easy to rinse and clean thanks also to smooth internal finishes.



IPC